



6 Volt Recessed Gimbal GS Series

The **GS Series** combines the function of a well designed emergency lighting fixture with the style of a desirable looking recessed downlight. Several models and lamp choices provide flexibility in the emergency lighting layout while keeping an aesthetically pleasing look to the interior.

UL Listed

Complies with NEC, Life Safety Code and OSHA. Approved use in the Commonwealth of Pennsylvania and New York City.

Sealed Maintenance-Free Batteries

- Nickel Cadmium
- Lead Calcium
- Long life lead

Standard Features

Reliability

The GS Series comes complete with a 3-year full warranty.

Unit Data

Low Profile Trim Ring*, molded in tough polycarbonate, has a semi-gloss white finish to complement a variety of ceilings.

Adjustable Gimbal directs the light from one PAR 36 lamp.

Inconspicuously Mounted but Easily Accessed... the test switch and LED pilot light are located on the side of the lamp ring standard**.

Easy To Install... A slide out chassis and two quick-connect plugs make installation and servicing easy. Adjustable hanger bars are supplied with each unit.

PulsePlus Charger

PulsePlus circuitry offers 120/277 volt input 60 Hz., 0.3 Amp, fused output circuit(s), long life LED pilot indicator, temperature compensated, sealed relay, low voltage battery disconnect, brownout protection and lockout (automatic battery connect).

Optional Features

Description

New York City (12 watt lamp).....-NYC

Add Suffix

How To Order (example)

For standard units without options only order Series, Battery, and Watts

Options are added to units by listing suffix at end of model #

GS - C - 18 - BH - *(ZD) - NYC

Series	Battery Type	Watts	Bar Hanger	Lamp Option	NYC Approved Model
GS	Long life lead	for 90 min.	BH	6V 9W incandescent	NYC

Includes standard lamp

*see lamp data sheet in lighting fixture section for other lamp wattages.

* NYC version includes a metal trim and pivot assy.

** NYC version has the test switch and pilot lamp located on the gimbal ring.



Unit Rating Chart

Each unit is furnished with one 6 volt 9 watt wedge-base lamp. Other wattages available, see lamp data sheet for selection of PAR lamps only.

UNIT EQUIPMENT - NO REMOTE CAPABILITY						
Sealed Maintenance-Free Battery Types	D.C. Voltage	Model Number	*Watts to 87 1/2% of rated battery voltage			
			11/2 hrs.	2 hrs.	3 hrs.	4 hrs.
Lead calcium	6	GSM9-BH	9	6	-	-
Long life lead	6	GSE9-BH	9	7	-	-
UNIT EQUIPMENT - WITH REMOTE CAPABILITY						
Nickel cadmium	6	GSC18-BH	18	12	9	6
Long life lead	6	GSE18-BH	18	11	8	6

*National Electrical Code Specification

☐ New York City Approved

Outline and Dimensions

Dimensions are approximate and subject to change.

