## **Commercial Products**

## Series Features

	Integrated Solid State System								
	<ul> <li>Multi-Rate, Controlled, Automatic Charger</li> </ul>								
	Lock Out (Automatic Battery Connect)								
	Low-Voltage Battery Cutoff								
	Brownout Sensitivity								
	Fused AC Input & DC Output Circuit Protection								
	Dual-Voltage Transformer for 120/277 VAC Operation								
	Maximum Input Rating								
	120VAC 60 Hz 0.35 Amps								
	277VAC 60 Hz 0.15 Amps								
	HIT Lamps     STD Lamp: See Unit Information								
<b>V</b>	PAR-36 Sealed Beams								
<u>الله</u>	Sealed Lead Calcium Battery								
	6- or 12-Volt Operation								
	Maintenance-Free								
	Fully Recessed Styling								
	Designed for Use in 2-Foot Grid (T-Bar) Drop Ceilings								
4	Easy Access Battery Panels								
$\square$	20-Gauge Steel Housing								
	Unit Mounts Up to 4 Lamp Heads								
	White Powder-Coat Finish								
	Red (Power On) LED Indicator								
	Test Switch								
	UL Listed								
	New York City Approved/Calendar #38236								

## Unit Information

Model	Std. Lamp Watt	Watts per Hour								Replacement
Number		1.5	2	3	4	5	6	7	8	Battery
2BR6S8	8	18	14	9	7	-	-	-	-	(1) <b>S68</b>
H2BR6S10†	12	32	24	16	12	10	8	7	6	(1) S610SL
2BR6S16	8	45	36	20	15	12	10	9	8	(2) S68
2BR6S20	8	64	50	32	24	19	16	14	12	(2) S610SL
2BR6S36	8	100	75	50	38	30	25	21	18	(1) S636
H2BR12S7†	12	36	27	18	14	11	9	8	7	(2) S68
H2BR12S10+	12	60	45	36	23	18	15	13	11	(2) S610SL
H2BR12S15†	12	100	75	50	38	30	25	21	18	(1) S1215
†Chicago Code Approved										

Illumination is rated to 87.5% of nominal system voltage and recharge to full capacity within 24 hours. <u>NEC requires 1.5 hours of emergency illumination.</u>

## Ordering Information


н	2	BR	12	S	15	-PA
Halogen Lamp Prefix	Lamp Heads on Unit (0,1,2,3,4)	Series	DC Battery Voltage	Battery Type (S – Sealed)	Battery Amp/Hour	Options




BR

Shown in Standard White Finish

Providing a clean look in commercial installations, the BR Series combines the advantage of a fully recessed unit with maximum remote head capability.





Options Add Suffix to Catalog Number

-BLK	Black Finish
-ow	Designer Off-White Finish
-PA	Plenum Construction
TD	Time Delay – Adjusts 1–60 min.
-**	Special Lamp Wattage (See page 50)



