




Series Features

- Integrated Solid State System
 - Multi-Rate, Controlled, Automatic Charger
 - Lock Out (Automatic Battery Connect)
 - Low-Voltage Battery Cutoff
 - Brownout Sensitivity
 - Dual-Voltage Transformer for 120/277 VAC Operation
 - Maximum Input Rating
120VAC 60 Hz 0.35 Amps
277VAC 60 Hz 0.15 Amps
-  ■ HIT Lamps STD Lamp: See Unit Information
- PAR-36 Sealed Beams
-  ■ Sealed Lead Calcium Battery (S) or Sealed Nickel Cadmium Battery (N)
- 6- or 12-Volt Operation
- Maintenance-Free
-  ■ Contemporary 3-D Design
- 20-Gauge Steel Housing
- Polycarbonate Lamp Heads (Rectangular)
- Steel Lamp Heads (Round)
- Universal Mount Backplate
- Beige Powder-Coat Finish Standard
- Red (Power On) LED Indicator
- Test Switch
- UL Listed
- New York City Approved/Calendar #32110



Round Heads



Rectangular Heads

Unit Information

Model Number	Std. Lamp Watt	Watts per Hour								Replacement Battery	Head Shape
		1.5	2	3	4	5	6	7	8		
2ET6S5	6	12	9	6	-	-	-	-	-	(1) S65	Rect.
2ET6S8	9	18	14	9	7	-	-	-	-	(1) S68	Rect.
2ET6S8-8	8	18	14	9	7	-	-	-	-	(1) S68	Round
H2ET6S10†	12	32	24	16	12	10	8	7	6	(1) S610SL	Round
H2ET6S16†	12	45	36	24	18	14	12	10	9	(2) S68	Round
H2ET12S7†	12	36	27	18	14	11	9	8	7	(2) S68	Round
2ET6N4	6	12	9	6	-	-	-	-	-	(1) N64F	Rect.
2ET6N7	9	25	18	14	9	-	-	-	-	(1) N67F	Rect.
2ET12N4	9	25	18	14	9	-	-	-	-	(2) N64F	Rect.
2ET12N7	9	50	36	24	18	14	12	10	9	(2) N67F	Rect.
H2ET6N4	6	12	9	6	-	-	-	-	-	(1) N64F	Round
H2ET6N7†	12	25	18	14	9	-	-	-	-	(1) N67F	Round
H2ET12N4†	12	25	18	14	9	-	-	-	-	(2) N64F	Round
H2ET12N7†	12	50	36	24	18	14	12	10	9	(2) N67F	Round

†Chicago Code Approved

Illumination is rated to 87.5% of nominal system voltage and recharge to full capacity within 24 hours.

NEC requires 1.5 hours of emergency illumination.

Ordering Information

H	2	ET	6	S	10	TD
Halogen Lamp Prefix	Lamp Heads on Unit (0,1,2,3)	Series	DC Battery Voltage	Battery Type (S - Sealed) (N - Ni Cad)	Battery Amp/Hour	Options

Dimensions

ET

Height: 12.0"
Width: 13.1"
Depth: 2.9"

Options

Add Suffix to Catalog Number

- A Ammeter*
- BLK Black Finish
- HMC Heads Mounted on Cover
- HOS Heads Mounted on Sides
- OW Designer Off-White Finish (Round Heads Only)
- P2 Cord & Plug for 120VAC Input
- QC Quik-Chek™ Remote Test & Time Delay
- TD Time Delay - Adjusts 1-60 min.
- V Voltmeter*
- W White Finish
- WG Wood Grain Front Panel
- ** Special Lamp Wattage (See page 50)

*Choose Only One

The ET Series is an ideal choice for commercial applications where ease of installation, reliability, and moderate remote loads are required.

