



**Dimensions**

**HE**

Height: 12.0"  
Width: 15.0"  
Depth: 8.8"

The HE Series is designed for use in Class I, Division I hazardous areas. Lighting fixtures and exit fixtures are available for mounting directly to the housing or can be remotely mounted.

**Series Features**

	<p><b>NEC ENVIRONMENT RATINGS</b></p> <ul style="list-style-type: none"> <li>Meets or Exceeds UL Specifications for Use in the Following Areas: Class I, Division I, Groups C &amp; D Class II, Division I, Groups E, F &amp; G Class III</li> </ul>
	<ul style="list-style-type: none"> <li>Integrated Solid State System</li> <li>Controlled, Automatic Charger</li> <li>Dual-Voltage Transformer for 120/277 VAC Operation</li> </ul>
	<ul style="list-style-type: none"> <li>PAR-36 Halogen Sealed Beam Lamps, 6-Volt – 12-Watt</li> </ul>
	<ul style="list-style-type: none"> <li>Sealed Nickel Cadmium Battery (N)</li> <li>6- or 12-Volt Operation</li> <li>Maintenance-Free</li> </ul>
	<ul style="list-style-type: none"> <li>Completely Self-Contained Operation</li> <li>Heavy Cast, Copper-Free Aluminum Housing</li> <li>Sealed Test Switch</li> <li>Power On Indicator</li> <li>UL-Listed Enclosures and Fixtures</li> </ul>

**Ordering Information**

HE Series	12 DC Battery Voltage	N Battery Type	14 Battery Amp/Hour
-----------	-----------------------	----------------	---------------------

**Unit Information**

Model Number	Std. Lamp Watt	Watts to 87.5% of System Voltage				Sealed Battery Type
		1.5 hrs.	2 hrs.	4 hrs.	8 hrs.	
HE6N7	6	25	16	7	–	Nickel Cadmium
HE6N14	6	50	38	19	9	
HE6N21	6	75	56	28	14	
HE6N28	6	100	75	38	19	
HE6N56	6	200	150	76	38	
HE12N7	12	50	38	19	9	
HE12N14	12	100	75	38	19	
HE12N28	12	200	150	76	38	

For remote fixture applications, use one of the above power units and remote fixtures/exits on page 53. Remote fixtures/exits must be the same DC voltage and total remote wattage must not exceed the 1.5-hour capacity of the above power unit. 12-volt equipment is suggested for longer wire runs.

**6-Volt Hazardous Area Emergency Lighting Power Units Complete with Batteries and Chargers**



**HE6N7-1EP-H20**  
 ■ Single-head unit with 20-watt halogen lamp



**HE6N7-1XP1R-H20**  
 ■ Single exit fixture with 20-watt halogen lamp



**HE6N7-2EP-H10**  
 ■ Double-head unit with 10-watt halogen lamp



**HE6N7-1EP-1XP1R-H10**  
 ■ Single-head & single exit w/10-watt halogen lamp

**HE6N14-2EP-H20**  
 ■ Double-head unit with 20-watt halogen lamp

**HE6N14-1EP-1XP1R-H20**  
 ■ Single-head & single exit w/20-watt halogen lamp

For power units with lighting heads and/or exit fixtures mounted directly to the housing, choose from the models listed above. These units are supplied with a swivel elbow for each lighting fixture. Conduit is to be supplied by the installer.