



CEILING MOUNTED WITH ELF-645 DECORATIVE CYLINDERS.


Decorative Style Equipment
6 and 12 Volt Maintenance-Free Lead Calcium, Long-Life Lead or Nickel Cadmium Batteries



NRTL. UL 924



6 and 12 Volt Decorator Recessed



CEILING MOUNTED WITH ELF2 DECORATIVE HEADS.

features

- **CONSTRUCTION:**
Construction of 20 gauge steel with an off-white baked enamel finish. Furnished with ELF-645 or ELF-2 heads with 6 or 12 volt lamps as specified.
- **MOUNTING:**
Easily recesses into wall or ceiling. Mounting brackets included for installation in grid type suspended ceilings. Bar hangers included.
- **ELECTRONICS:**
 - Automatic, temperature compensated, pulse type charger.
 - High capacity, automatic, dust tight instantaneous transfer relay.
 - Low voltage disconnect prevents over discharge of battery. Automatic brown out protection is provided.
 - Labor saving AC line latch prevents battery discharge during installation to a non-energized circuit.

battery

6 or 12 volt maintenance-free, sealed lead calcium, long life lead or nickel cadmium.

options

Description (Add suffix to model number)	Suffix
Ammeter OR Voltmeter (Choose only one)	A* OR V*
Improved Diagnostics	ID
Improved Diagnostics (non-audible)	IDNA
Time Delay	TD**
ELF2 Lighting Heads	ELF2
Non-Standard Input Voltage.....	Specify
New York City (ELF645 heads)	NY
*Not available with Diagnostics option	
**Not required when using the ID option	

Accessories

(Order as a separate item)

Model	
Wire Guard (ELF645 or ELF2 heads)	WG6
27" Adjustable Bar Hangers	BH-RD

Note: Certain option combinations may effect the UL listing. Please contact the factory for specifics.

unit selection chart

Standard lamp is 6 or 12 volt 9 watt wedge base

UNIT EQUIPMENT - NO REMOTE CAPABILITY								
Sealed Maintenance-Free Battery Types	D.C. Voltage	Model Number		*Watts to 87 1/2% of rated battery voltage 1 1/2 hrs. 2 hrs. 3 hrs. 4				
		ELF-645 Lamps Heads	ELF-2 Lamp Heads					
Nickel Cadmium Δ	6	2RD6C1**	2RD6C1-ELF2	18	12	10	-	
Long Life Lead Δ	6	2RD6E1	2RD6E1-ELF2	18	11	8	-	
Lead Calcium Δ	6	2RD6M1	2RD6M1-ELF2	18	12	9	-	
UNIT EQUIPMENT - WITH REMOTE CAPABILITY								
Nickel Cadmium Δ	6	2RD6C2**	2RD6C2-ELF2	25	18	12	9	
	Δ	12	2RD12C3**	2RD12C3-ELF2	36	21	15	12
Long Life Lead Δ	6	2RD6E2	2RD6E2-ELF2	27	19	14	10	
	Δ	6	2RD6E3	2RD6E3-ELF2	36	24	17	13
	Δ	12	2RD12E3	2RD12E3-ELF2	36	24	17	13
	Δ	6	2RD6M2	2RD6M2-ELF2	27	18	14	10
Lead Calcium Δ	6	2RD6M3	2RD6M3-ELF2	36	25	20	14	
	Δ	6	2RD12M3	2RD12M3-ELF2	36	25	20	14
	Δ	12	2RD12M3	2RD12M3-ELF2	36	25	20	14


*National Electrical Code Specification

Δ = Improved Diagnostics Available

** CSA NRTL UL924 Listed

dimensions

Dimensions are approximate and subject to change.



ordering format

For standard units without options only order Series, Battery, Watts and Heads *Options are added to units by listing suffix at end of model #*

2	- RD	- 12	- C	- 3	- *L9	- TD
No. of heads	Series	DC Battery backup	Battery Type Ni-cad	Capacity indicator	Lamp Option Incandescent	Option 6V 9W Time Delay
Includes Standard Lamp						

*see lamp data sheet in lighting fixture section for other lamp wattages.