

## Series Features




- Integrated Solid State System
- Multi-Rate, Controlled, Automatic Charger
- Lock Out (Automatic Battery Connect)
- Low-Voltage Battery Cutoff
- Brownout Sensitivity
- Dual-Voltage Transformer for 120/277 VAC Operation
- Maximum Input Rating  
120VAC 60 Hz 0.20 Amps  
277VAC 60 Hz 0.20 Amps



- High-Intensity Tungsten Lamps, 6-Watt



- Sealed Lead Calcium Battery
- 6-Volt Operation
- Maintenance-Free



- Compact Design
- Flame-Retardant Noryl 190® Housing
- Universal-Mount, Galvanized Steel Backplate
- High-Impact, Mist-White Finish
- Wall or Ceiling Mount
- Red (Power On) LED Indicator
- Test Switch
- Damp Location Listed
- UL Listed

## Unit Information

Model Number	Std. Lamp Watt	Watts per Hour								Replacement Battery
		1.5	2	3	4	5	6	7	8	
2PH6S5	6	12	9	6	-	-	-	-	-	(1) S65

Illumination is rated to 87.5% of nominal system voltage and recharge to full capacity within 24 hours.

NEC requires 1.5 hours of emergency illumination.

## Ordering Information

2	PH	6	S	5
Lamp Heads on Unit	Series	DC Battery Voltage	Battery Type (S – Sealed)	Battery Amp/Hour



Designed so that lamp head assemblies can be adjusted to the "UP" position or to the sides.

## Dimensions

### PH

Height: 7.15"  
Width: 11.25"  
Depth: 6.95"

