



XC-R Series

6 VOLT MODELS 10 - 26 WATTS

MODEL	DIMENSIONS
XC-R XC-R-3 XC-R-5	3 1/4"D x 13"W x 9 1/4"H

Application

High-Lites XC-R Recessed Emergency Light is designed for installation in drywall or suspended ceiling applications. The XC-R is an attractive, low profile unit that will blend in with any decor.

Standard Features

- Die-formed heavy gauge steel.
- Dual 120 or 277 VAC input, field selectable.
- 1-1/2 hours of light to an end battery voltage of 87-1/2% of nominal voltage.
- 100% solid-state switching circuit.
- Solid-state line-latched low voltage disconnect circuit provides DC load disconnect protection to guard against battery deep discharge.
- Solid-state short circuit and overload protection on DC output circuit.
- Momentary test switch.
- AC ready light.
- AC lockout feature reduces installation time.

Batteries

Provided with each High-Lites Emergency Light is a long-life Lead Calcium maintenance free battery that will provide many years of dependable service. Optional Pure Lead and Nickel Cadmium batteries are available. Consult factory.

Lamps And Heads

High intensity incandescent lamps maximize light output through a specially designed lens to provide for glare free light distribution. Lighting heads are fully adjustable.

aOptions

Add	Description
-V*	Voltmeter
-A*	Ammeter
-220	220-50Hz VAC Input
-SX	Self-Diagnostic Circuit

* Provision for one meter only

Unit Selection Chart

Model No.	Volts	Capacity in Watts to 87-1/2% Nominal Voltage				Std. Lamp
		1-1/2 HRS.	2 HRS.	3 HRS.	4 HRS.	
XC-R	6	10	—	—	—	5 watts incandescent (-25) (each head)
XC-R-3	6	16	15	13	9	
XC-R-5	6	26	20	15	12	